

SPECIFICATION

Model	NS-1228A	NS-1245A
Input voltage	AC 110V or 220V +/- 10% switchable	
Input frequency	47 - 63 Hz	
Polarity	Negative	
Output voltage	9 - 15V adjustable	
Continuous (13.8V)	25A	40A
Surge (13.8V)	28A	45A
Overvoltage protection	16V +/- 0.5V	
Ripple & Noise	Peak to peak ripple & noise < 0.3%	
Efficiency	75%	
Dimension L/W/H (mm)	170x145x110	220x227x145
Net Weight	1.8Kg	4Kg

FEATURE

- Short circuit and over voltage protection
- Output power rated at continuous service
- Binding post output terminals
- Precision regulation of output voltage
- Low peak-peak ripple of less than 0.3%
- External fuse access
- High surge capacity
- Heavy duty metal cabinet with power coating
- Backlight LED with blue, vintage yellow, or white

NS-1228A Photo



APPLICATION

- Communications equipment
- Auto mobile sound systems
- Test equipment and appliances
- Portable entertainment equipment and appliance
- Vehicle accessories and Dclighting systems
- Security systems and CCTV
- Amateur electro plate
- Cooler boxes

NS-1245A Photo



Taiwan Nissei Sokki Co. Ltd.

No. 2, LN 21, Cheng Kong Rd., Panchiao, Taipei, Taiwan

TEL : 886-2-29626195 FAX : 886-2-29577492

email : info@nissei.com.tw www.nissei.com.tw